AVJ42-KBEP

Adjustable-Height Steel Cart with **Battery-Powered Device Charger**


Product Specifications -Cart and Device Charger Bundle

Item Number	AVJ42-KBEP
Shipping Method	Ground
Shipping Carton Dimensions: Box 1: AVJ42 Box 2: KBEP-BRKT-M Box 3: KBEP-2B1C1	25" W x 22" D x 19" H 13" W x 12" D x 4" H 21" W x 12" D x 9" H
Shipping Weight: Box 1: AVJ42 Box 2: KBEP-BRKT-M Box 3: KBEP-2B1C1	56 lbs. 3 lbs. 13 lbs.

To Order, Call Your **Sales Representative** or 800-323-4656

Product Specifications -Adjustable-Height Steel AV Cart

Item Number	AVJ42
Material	Powder-Coated Steel
Color	Black
Cart Dimensions	24" W x 18" D x 24-42" H
Distance Between Shelves	Lower to Middle: 14.75" Middle to Top: Adjustable, 0.5" - 16"
Retaining Lip	Yes; 0.25"
Safety Mats	Yes
Grommet Holes	Two; one each on middle and top shelf
Casters (4)	4" silent roll, swivel, ball-bearing; two with locking brakes
Power	Three-outlet power strip; UL/CSA Listed
Voltage	120V/15A
Cord Length	15'
Total Weight Capacity (Evenly Distributed)	75 lbs.
Made in USA	Yes
Product Weight	62.5 lbs.
Assembly Required	Yes
Warranty	5-year limited warranty



Total Weight Capacity (Evenly Distributed): 75 lbs. Weight Capacity Per Shelf:




AVJ42-KBEP


Adjustable-Height Steel Cart with Battery-Powered Device Charger

Product Specifications -

KwikBoost EdgePower® Desktop Charging Station System

Item Number	KBEP-2B1C1
AC Outlet Output	Output: 100V-120V, 60Hz, modified sine wave
	Continuous Output Power: 90W
	Peak Output Power: 95W (10 minutes)
USB Output	USB-A Port: 5V 2.4A (12W) - Quick Charge 3.0 Technology
	USB-C PD Port: 5V 2A (10W), 12V 1.5A (18W)
Single Battery Charger Input	100-240V 50/60Hz (2A)
Charging Output to Battery	25.5V 3.0A
Battery Capacity	146.52Wh (18 cells)
Cell Type	18650 Li-ion battery (2200mAh at 3.7V)
Life Cycles	500 times (higher than 80% of the initial capacity)
Shelf-Life	1 year after first charge
Battery Shipping Classifications	UN 3480
Battery Cell Recharge Time	2 hours
Desktop Charging Unit Weight	1.8 lbs.
Rechargeable Battery Weight	2.8 lbs.
Single Battery Charger Weight	1.0 lb.
Desktop Charging Unit Dimensions	0 211 D (10 211 with battom incorted)
Desicop charging offic difficusions	8.3" D (10.3" with battery inserted) x 4.9" W x 5.2" to 6" H (based on clamp setting)
Charging Unit Clamp Height Range	x 4.9" W x 5.2" to 6" H (based on
, 00	x 4.9" W x 5.2" to 6" H (based on clamp setting)
Charging Unit Clamp Height Range	x 4.9" W x 5.2" to 6" H (based on clamp setting) 0.7" to 1.5"
Charging Unit Clamp Height Range Rechargeable Battery Dimensions	x 4.9" W x 5.2" to 6" H (based on clamp setting) 0.7" to 1.5" 9.1" D x 3.0" W x 2.1" H
Charging Unit Clamp Height Range Rechargeable Battery Dimensions Single Battery Charger Dimensions	x 4.9" W x 5.2" to 6" H (based on clamp setting) 0.7" to 1.5" 9.1" D x 3.0" W x 2.1" H 0.75" D x 3.25" W x 2.25" H Limited one (1) year from date
Charging Unit Clamp Height Range Rechargeable Battery Dimensions Single Battery Charger Dimensions Warranty	x 4.9" W x 5.2" to 6" H (based on clamp setting) 0.7" to 1.5" 9.1" D x 3.0" W x 2.1" H 0.75" D x 3.25" W x 2.25" H Limited one (1) year from date of shipment
Charging Unit Clamp Height Range Rechargeable Battery Dimensions Single Battery Charger Dimensions Warranty Certifications	x 4.9" W x 5.2" to 6" H (based on clamp setting) 0.7" to 1.5" 9.1" D x 3.0" W x 2.1" H 0.75" D x 3.25" W x 2.25" H Limited one (1) year from date of shipment FCC, ETL 32° to 113°F (0° to 45°C); Discharge
Charging Unit Clamp Height Range Rechargeable Battery Dimensions Single Battery Charger Dimensions Warranty Certifications Operating Temperatures Charging	x 4.9" W x 5.2" to 6" H (based on clamp setting) 0.7" to 1.5" 9.1" D x 3.0" W x 2.1" H 0.75" D x 3.25" W x 2.25" H Limited one (1) year from date of shipment FCC, ETL 32° to 113°F (0° to 45°C); Discharge 14° to 131°F (-10° to 55°C) Temperature, short circuit, overcharge,





To Order, Call Your Sales Representative or 800-323-4656

US Patent # 112889935

